

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **TEKFLEX LIQUID**

Recommended Use of the Chemical and Restrictions on Use Used in conjunction with Tekflex Powder to form an hydraulic cement for a flexible strata support membrane.

Supplier: Minova Australia Pty Ltd
ABN: ABN: 084 965 962
Street Address: 102 Albatross Road,
Nowra, NSW 2541
Australia

Telephone Number: 1300 MINOVA (1300 646 682)
Facsimile: 1300 FAXMINOVA (1300 329 646)
Website: www.minovaglobal.com

Emergency Telephone: **1800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Sensitisation - Category 1

SIGNAL WORD: WARNING



Hazard Statement(s):

H317 May cause an allergic skin reaction.

Precautionary Statement(s):

Prevention:

P261 Avoid breathing mist, vapours, spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye and face protection.

Response:

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see First Aid Measures on Safety Data Sheet).
P363 Wash contaminated clothing before re-use.

Storage:

No storage statements.

Safety Data Sheet

**Disposal:**

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Synthetic polymer(s)	-	30-60%	-
Water	7732-18-5	30-60%	-
Vinyl acetate	108-05-4	<0.5%	H225 H332 H335 H341 H351 H402
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	<=0.003%	H331 H311 H301 H314 H317 H400 H410

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water and soap. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Unsuitable Extinguishing Media:

Water jet.

Specific hazards arising from the chemical:

Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes, including those of oxides of carbon.

Safety Data Sheet



Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and out of direct sunlight. Store between 5°C and 40°C. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Vinyl acetate: 8hr TWA = 35 mg/m³ (10 ppm), 15 min STEL = 70 mg/m³ (20 ppm)

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Safety Data Sheet



Appropriate engineering controls:

Ensure ventilation is adequate to maintain air concentrations below Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.



Wear overalls, safety glasses and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid Emulsion
Colour:	Whitish
Odour:	Faint
Odour Threshold:	Not available
Solubility:	Miscible in water.
Specific Gravity:	1.07 @ 20°C
Relative Vapour Density (air=1):	Not available
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	Not applicable
Flammability Limits (%):	Not applicable
Autoignition Temperature (°C):	Not applicable
% Volatile by Weight:	45% (water)
Solubility in water (g/L):	Complete
Melting Point/Range (°C):	Not available
Boiling Point/Range (°C):	Not available
Decomposition Point (°C):	Not available
pH:	4.5 - 6.5
Viscosity:	Not available
Partition Coefficient:	Not available

10. STABILITY AND REACTIVITY

Reactivity: No hazardous reactions if stored and handled as prescribed/indicated.

Product Name: TEKFLEX LIQUID
Substance No: 000000052023

Issued: 28/07/2017
Version: 3

Safety Data Sheet



Chemical stability:	Stable under normal conditions of use.
Possibility of hazardous reactions:	None known.
Conditions to avoid:	Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with strong oxidising agents.
Hazardous decomposition products:	Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	No adverse effects expected, however, large amounts may cause nausea and vomiting.
Eye contact:	May be an eye irritant.
Skin contact:	Contact with skin may result in irritation. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
Inhalation:	Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes of the respiratory tract, headache and nausea.

Acute toxicity: No LD50 data available for the product.

Skin corrosion/irritation:	Non-irritant. (1)
Serious eye damage/irritation:	Non-irritant. (1)
Respiratory or skin sensitisation:	A skin sensitizer.

Chronic effects: No information available for the product.

Mutagenicity:	Not classified.
Carcinogenicity:	Not classified.
Reproductive toxicity:	Not classified.
Specific Target Organ Toxicity (STOT) - single exposure:	Not classified.
Specific Target Organ Toxicity (STOT) - repeated exposure:	Not classified.
Aspiration hazard:	Not classified.

For vinyl acetate: This material has been classified by the International Agency for Research on Cancer (IARC) as a Group 2B. Group 2B - The agent is possibly carcinogenic to humans.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
--------------------	--------------------------------

13. DISPOSAL CONSIDERATIONS

Product Name: *TEKFLEX LIQUID*
Substance No: *000000052023*

Issued: *28/07/2017*
Version: *3*

Safety Data Sheet



Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Sensitisation - Category 1

Hazard Statement(s):

H317 May cause an allergic skin reaction.

Poisons Schedule (SUSMP): None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS) or are exempt.

16. OTHER INFORMATION

(1) Supplier Safety Data Sheet; 10/ 2014.

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

Reason(s) for Issue:

Revised Primary SDS
Change in company details
Change in Hazardous Chemical Classification
Updated Formulation
Update in Toxicological Information

Safety Data Sheet



This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since The Supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Supplier representative or The Supplier at the contact details on page 1.

The Supplier's responsibility for the material as shipped is subject to the terms and conditions of sale, a copy of which is available upon request.